19" Equipment Rack



TR-2201

- 19" MOUNTING STANDARD EQUIPMENT RACK
- Suitable for good load-carrying capacity
 - Detachable side panel
 - Finished in 2-tone grey epoxy powder paint
 - Lockable Rear Door, front Perspex Door or Tempered Safety Glass Door
 - Available from 15U through 46U
 - 700mm Depth (Standard), optional in 800mm 1000mm Depth
 - Standard accessories including PVC Trunking, 13AMP Power Point Channel complete with socket, PMM Mounting Member, Panel Mounting Member and M6 x 12mm caged nuts with screws





TR-2201

- 19" MOUNTING EQUIPMENT RACK COMPLETE WITH CABLE MANAGEMENT
- Suitable for patch cable management
- Side vertical cable management panel
- Detachable side panel
- Finished in 2-tone grey epoxy powder paint
- Lockable Rear Door, front Perspex Door or Tempered Safety Glass Door
- Available from 15U through 46U
- 700mm Depth (Standard), optional in 800mm 1000mm Depth
- Standard accessories including 13
 AMP Power Point Channel complete
 with socket, PMM Mounting Member,
 Panel Mounting Member and M6 x
 12mm caged nuts with screws

STANDARD

Width	1U 44.45mm Height U	Overall H (mm)	Usable H (mm)	Nos of 13AMP Socket Point	Weight (KG)	
(mm)					Depth 700mm	Depth 800mm
600	15	825	667	4	58	66
600	18	958	800	5	67	76
600	24	1225	1067	6	86	98
600	27	1358	1200	8	95	109
600	33	1625	1467	10	114	130
600	37	1803	1645	12	126	144
600	42	2025	1867	12	142	162
600	46	2203	2045	14	154	176

COMPLETE WITH CABLE MANAGEMENT

Width	1U 44.45mm	Overall H Usable H Nos of 13A		Nos of 13AMP	Weight (KG)	
(mm)	Height U	(mm)	(mm)	Socket Point	Depth 700mm	Depth 800mm
692	15	850	667	4	69	78
692	18	983	800	5	79	91
692	24	1250	1067	6	101	115
692	27	1383	1200	8	112	128
692	33	1650	1467	10	133	152
692	37	1828	1645	12	147	169
692	42	2050	1867	12	165	189
692	46	2228	2045	14	180	205